CLAIM SUMMARY DOCUMENT

- 1. (Currently Amended) A lube base oil comprising:
 - a) at least one synthetic lube base oil having an iso-paraffin content greater than
 50 % and an Oxidator A value in the absence of additives of less than about
 1; and
 - at least one percent of a non-synthetic lube base oil selected from the groups consisting of Group I lube base oils, Group II lube base oils with a sulfur content greater than about 50 ppm, petroleum-derived Group V lube base oils, or mixtures thereof wherein the non-synthetic lube base oil has an Oxidator BN value in the presence of additives of less than about 7; wherein the lube base oil has a greater stability an Oxidator A value in the absence of additives than the stability of the synthetic lube base oil of greater than about 1 and has a greater stability an Oxidator BN value in the presence of additives than the non-synthetic lube base oil of greater than about 7.
- 2. (Original) A lube base oil according to claim 1 wherein the synthetic lube base oil is prepared by the Fischer Tropsch process.
- 3. (Original) A lube base oil according to claim 1 wherein the synthetic lube base oil is present in an amount of about 20 to about 80 % by volume.
- 4. (Currently amended) A lube base oil comprising:
 - a) at least one synthetic lube base oil having a sulfur content less than about 50 ppm and an Oxidator A value in the absence of additives of less than about 1; and
 - b) at least one percent of a non-synthetic lube base oil having a sulfur content greater than about 300 ppm and selected from the groups consisting of Group I lube base oils, petroleum-derived Group V lube base oils, or mixtures thereof wherein the non-synthetic lube base oil has an Oxidator BN value in the presence of additives of less than about 7; wherein the lube base oil has a greater stability an Oxidator A value in the absence of additives than the stability of the synthetic lube base oil of greater than about 1 and has a

greater stability an Oxidator BN value in the presence of additives than the non-synthetic lube base oil of greater than about 7.

- 5. (Original) A lube base oil according to claim 4 wherein the synthetic lube base oil is prepared by the Fischer Tropsch process.
- 6. (Original) A lube base oil according to claim 4 wherein the non-synthetic lube base oil has a sulfur content greater than about 700 ppm.
- 7. (Original) A lube base oil according to claim 4 wherein the synthetic lube base oil has an Oxidator BN value in the presence of additives greater than 7.
- 8. (Original) A lube base oil according to claim 7 wherein the synthetic lube base oil has an Oxidator BN value in the presence of additives greater than 10.
- 9. (Original) A lube base oil according to claim 4 wherein the non-synthetic lube base oil has an Oxidator A value in the absence of additives greater than about 5.
- 10. (Currently amended) A lube base oil comprising:
 - a) at least one synthetic lube base oil having an Oxidator A value of less than about 1 in the absence of additives and an Oxidator BN value greater than about 7 in the presence of additives; and
 - a non-synthetic lube base oil having an Oxidator A value greater than about 5 in the absence of additives and an Oxidator BN value less than about 10 in the presence of additives;

wherein the lube base oil has a greater stability an Oxidator A value in the absence of additives than the stability of the synthetic lube base oil of greater than about 5 and has a greater stability an Oxidator BN value in the presence of additives than the non-synthetic lube base oil of greater than about 10.

- 11. (Original) A lube base oil according to claim 1 wherein the oil has an oven storage stability of greater than 90 days when measured at 150°F.
- 12. (Original) A lube base oil according to claim 1 wherein the synthetic oil is used in an amount of about 50 % to about 99% and the non-synthetic oil is used in amount of about 50 % to about 1%.
- 13. (Newly added) A lube base oil according to claim 1, wherein the lube base oil has an Oxidator A value in the absence of additives of greater than about 5 and an Oxidator BN value in the presence of additives of greater than about 10.

14. (Newly added) A lube base oil according to claim 13, wherein the lube base oil has an Oxidator A value in the absence of additives of greater than about 10.